PRIVACY-PRESERVING DATABASE TUNING

BALANCING PRIVACY & PERFORMANCE WITH ENDURE

TABLE OF CONTENTS

BOSTON UNIVERSITY

PAPER OVERVIEW

1	Motivation
2	Background
3	Experiment Design
4	Results
5	Conclusion

PRIVACY-PRESERVING DATABASE TUNING
BOSTON UNIVERSITY

MOTIVATION

MOTIVATION BOSTON UNIVERSITY

PRIVACY RISKS IN LSM-TREE DATABASES

- LSM-Tree Databases: Power data-driven apps like e-commerce platforms with efficient key-value operations
- Privacy Issue: Workload statistics are used to tune these systems, which can leak sensitive user information
- Example: In an e-commerce platform, a spike in write operations to a key range might reveal a user frequently buying medical supplies, hinting at a health condition
- Consequence: Attackers can infer personal details without accessing the data itself, just by analyzing workload patterns

MOTIVATION BOSTON UNIVERSITY

DIFFERENTIAL PRIVACY AS A SOLUTION

- Differential Privacy (DP): Adds noise to workload statistics to protect individual user data
- How It Works: In the e-commerce example, DP might adjust the write operation statistic (e.g. $0.2 \rightarrow 0.22$), masking individual actions
- Benefit: Preserves aggregate trends for system tuning while making it statistically impossible to infer personal details
- Our Goal: Quantify DP's impact on tuning, optimize noise levels, and enhance Endure to balance privacy and performance

PRIVACY-PRESERVING DATABASE TUNING BOSTON UNIVERSITY

BACKGROUND

MOTIVATION BOSTON UNIVERSITY

CORE COMPONENTS

LSM Trees

- \circ Storage engine in systems like RocksDB, Cassandra \rightarrow known for high write throughput
- Structure: Data organized in levels, with merging (compaction) of sorted runs to optimize reads
- Key Parameters: Size ratio, merge policy (tiering vs. leveling), memory for Bloom filters
- Tuning Need: Performance depends on workload-based tuning (e.g. Bloom filter allocation)

Endure's Robust Tuning

- Addresses workload uncertainty by modeling a neighborhood of probable workloads
- Goal: Compute configurations maximizing worst-case throughput across the neighborhood
- Traditional Assumption: **Expected workload is known**, with potential deviations

Differential Privacy (DP)

- Framework to release aggregate statistics without revealing individual data
- Mechanism: Add noise to workload proportions
- o Privacy Parameter (ε): Smaller ε increases privacy by adding more noise, perturbing the workload
- Goal in LSM Tuning: Prevent inference of individual user operations from the workload distribution

PRIVACY-PRESERVING DATABASE TUNING BOSTON UNIVERSITY

EXPERIMENT DESIGN


PROJECT WORKFLOW

Uncertainty

Parameter

Workload

Proportion Vector



Configuration

For Perturbed Workload

WORKLOAD PERTURBATION

- A perturb_workload function applies differential privacy to the workload vector Ω to produce Ω_ϵ
- $\Omega = [z_0, z_1, q, w]$
 - $\mathbf{z_0} = \%$ empty point lookups $|\mathbf{z_1}| = \%$ point lookups $|\mathbf{q}| = \%$ range queries $|\mathbf{w}| = \%$ writes
 - \circ $z_0 + z_1 + q + w = 1$
- $\Omega_{\epsilon} = [z'_{0}, z'_{1}, q', w']$
 - A Laplace distribution is used to perturb(add noise) the workload proportions

$$\hat{w}_i = w_i + \mathrm{Laplace}\left(rac{\Delta}{\epsilon}
ight)$$

- ∆ = sensitivity
- \circ ε = noise parameter
- The vector is then normalized to ensure $z'_0 + z'_1 + q' + w' = 1$


PROJECT WORKFLOW

Uncertainty

Parameter

Workload

Proportion Vector



Configuration

For Perturbed Workload

ENDURE'S UNCERTAINTY PARAMETER

What is ρ?

 \circ ρ is the uncertainty parameter in Endure and is what separates nominal and robust tuning

How ρ Improves Robustness

- \circ By tuning for a range of possible workloads, ρ ensures the configuration (Φ) can adjust to variation in workload during tuning
- A larger ρ prepares the system for greater uncertainty

ρ and Nominal Tuning

 When ρ approaches 0, the uncertainty region shrinks, and Endure's tuning becomes equivalent to nominal tuning (optimizing for the expected workload only)

Our Experiment with ρ

• We test how different ρ values (0.1, 0.3, 0.5, etc.) impact performance


PROJECT WORKFLOW

Uncertainty

Parameter

Workload

Proportion Vector



Configuration

For Perturbed Workload

ENDURE'S OPTIMAL LSM-TREE CONFIGURATION

What is Φ?

Φ is the optimized LSM tree configuration for the expected workload

Inputs to Φ

- \circ Workload: Either the original workload (Ω) or the perturbed workload (Ω_ε)
- Uncertainty Parameter (ρ)

Outputs of Φ

Optimal size ratio (T), memory allocation for Bloom filters (m_{filt}), and compaction policy (π) based on workload proportions


PROJECT WORKFLOW

Uncertainty

Parameter

Workload

Proportion Vector



Configuration

For Perturbed Workload

COST FUNCTION

What is the Cost Function?

 \circ The cost function C(Ω, Φ) measures the expected cost of a workload under a given Φ

$$C(\mathbf{w},\Phi) = z_0 Z_0(\Phi) + z_1 Z_1(\Phi) + q Q(\Phi) + w W(\Phi)$$

Inputs

- Original workload (w = Ω) or perturbed workload (w = Ω_{ϵ})
- o Baseline configuration (Φ) or private configuration (Φ_{ϵ})


Outputs of the Cost Function

A scalar cost value representing the performance of the configuration on the workload

How We Used It to Compare Performance

- Compared baseline performance with private performance to assess the impact of differential privacy
- Analyzed how different ρ values affect the performance gap between the two costs

PROJECT WORKFLOW




PRIVACY-PRESERVING DATABASE TUNING BOSTON UNIVERSITY

RESULTS

READ WORKLOADS


• Figure: Average Total Cost vs. Epsilon across Different Read Workloads.

Each line represents a different query mix profile (e.g., range-heavy, point-heavy, etc.). Results are averaged across 100 trials, with log-scaled Y-axis to highlight performance differences.




UNIFORM WORKLOADS


• Average Total Cost vs. Epsilon under uniform workload (equal z0, z1, q, w)



WRITE WORKLOADS


• Workload = [z0=0.01, z1=0.01, q=0.01, w=0.97] — Write-Intensive Profile





ρ PARAMETERIZATION

- Evaluate impact of ρ (robust tuning parameter) on total cost under DP
- Workload = Uniform [0.25, 0.25, 0.25, 0.25]



PRIVACY-PRESERVING DATABASE TUNING BOSTON UNIVERSITY

CONCLUSION

Conclusion

Differential privacy introduces real cost in LSM-tree tuning — especially under strong privacy (small ε).

- Workload sensitivity varies:
 - Range queries (q) and empty lookups (z0) are **most impacted** by noise.
 - Write-heavy workloads are more stable, but still require robust modeling.
- Robust tuning via ρ improves reliability:
 - High ρ guards against workload distortion and improves total cost under DP.
- No one-size-fits-all strategy:
 - Tuning depends on workload type, privacy budget, and tolerance for risk.
- Endure remains effective under DP when paired with careful parameterization.

THANK YOU