

CAS CS 591 A1: Data Systems Architectures Massive Data Algorithms and Systems Group Department of Computer Science College of Arts and Sciences, Boston University

https://midas.bu.edu/classes/CS591A1



CS591 A1 Spring 2020 - Systems Project

Title: *Implementation a LSM-Tree based key-value store*

Background: Log-structured merge-tree (LSM-trees) [1, 2, 3] are one of the most commonly used data structures for persistent storage of key-value entries. LSM-tree-based storages are in use in several modern key-value stores including RocksDB at Facebook, LevelDB and BigTable at Google, bLSM and cLSM at Yahoo!, Cassandra and HBase at Apache, and so on. LSM-trees store data in the disk as immutable logs (also known as sorted sequence tables (SSTs)), which are maintained in hierarchical levels of increasing capacity. To bound the number of logs that a lookup has to probe, LSM-trees merge logs of similar sizes. The two possible merging strategies are (i) leveling (optimized for lookups) and (ii) tiering (optimized for updates).

Objective: The objective of the project is to implement a LSM-tree using only a single process thread. The workflow for this is as the following.

- (a) Review LSM-tree literature to understand the principles and operations supported in an LSM-tree
- (b) Implement an LSM-tree (vanilla implementation) using only a single process thread¹¹ for both merging strategies leveling and tiering
- (c) Develop by cloning the API available to you at: https://github.com/midaslab-bu/cs591 templatedb. Note that you are expected to build a more extensive testing infrastructure.
- [1] Chen Luo, Michael J. Carey. **LSM-based storage techniques: a survey.** VLDB J. 29(1): 393-418 (2020)
- [2] Niv Dayan, Manos Athanassoulis, Stratos Idreos. **Monkey: Optimal Navigable Key-Value Store**. SIGMOD Conference 2017: 79-94
- [3] Patrick E. O'Neil, Edward Cheng, Dieter Gawlick, Elizabeth J. O'Neil. **The Log-Structured Merge-Tree (LSM-Tree)**. Acta Inf. 33(4): 351-385 (1996)

¹ In many LSM-tree-based storages (such as RocksDB, LevelDB) merging usually takes place as a multi-threaded background process in order to enhance the update performance. However, in this project, the goal is to implement LSM-trees using only a single thread.