

Class 16 : Joins I

Summary #pages M $\left(\begin{matrix} N \\ P_S \end{matrix} \right)$
 #rows per page P_R

$S(\underline{sid}, sname, rating, age)$
 $N=500 \quad P_S=80$
 $R(\underline{sid}, \underline{bid}, \underline{day}, vname)$
 $M=1000 \quad P_R=100$

Selection (a) i) cheapest access path
 ii) retrieve tuples
 iii) apply remaining selection conditions

(b) i) get rids from all matching indexes
 ii) intersection rids
 iii) retrieve tuples & apply remaining sel. and.

unsorted M I/Os
 sorted $\log_2 M + f \cdot M$
 clustered $\log_F M + f \cdot M$
 unclustered $\log_F M + f \cdot M \cdot P_R$

Projection
 sort + discard unwanted fields & duplicates
 hash + CC

cost: $M + 2 \cdot T \leftarrow$ pages after removing unwanted fields

Joins : Nested-Loop Joins
 Sort-Merge Joins today

any interesting query contains a join
 Hash Joins
 Remaining op (joins + agg)

SELECT * FROM R, S WHERE R.sid = S.sid

R ⋈ S discuss as # I/Os discard output

~~$\sigma_{R.sid=S.sid}(R \times S)$~~

• Simple Nested-Loop Join

R ⋈_{i=j} S

$\forall r \in R \leftarrow$ outer

$\forall s \in S \leftarrow$ inner

if $r_i = s_j$ then add $\langle r, s \rangle$ to the result

Cost

$$(M \cdot P_R) \cdot N + M = (1000 \cdot 100) \cdot 500 + 1000 = \boxed{50,001,000} \text{ \# I/Os}$$

\downarrow
rows of R 1 I/O \rightarrow 2ms $\boxed{28h}$

R $M=1000 \rightarrow 4\text{MB}$

S $N=500 \rightarrow 2\text{MB}$

swap R with S

$$(N \cdot P_S) \cdot M + N = \boxed{40,000,500} \text{ I/Os}$$

• Page-oriented Nested-Loop Join

\forall page b_r in R

\forall page b_s in S

\forall tuple r in b_r

\forall tuple s in b_s

if $r_i = s_j$ then add $\langle r, s \rangle$ to the result

Cost

$$M \cdot N + M = 1000 \cdot 500 + 1000 = \boxed{501,000} \rightarrow \boxed{17 \text{ min}}$$

smaller outer?

$$N \cdot M + N = 500 \cdot 1000 + 500 = \boxed{500,500}$$

Index Nested Loop Join

∀ tuple r in R

probe index to fetch s such that $s_i = r_j$

add $\langle r, s \rangle$ to result

Cost

$M + M \cdot PR$ • cost of finding matching tuples through the index

↳ Hash index 1.2 I/Os
↳ B⁺-Tree 2-4 I/Os

clustered → 1 I/O per page of matching tuples

unclustered → 1 I/O per matching tuple

Example 1: hash idx on side of S

Scan R : (M)

∀ each tuple in R

fetch data entry (1.2)

goto file (1)

$$M + M \cdot PR \cdot (1.2 + 1) \rightarrow \overset{1000 \cdot}{1000 \cdot 100} (2.2) = \boxed{221,000} \rightarrow \boxed{7 \text{ min}}$$

Example 2: hash idx on sid of R

$$\frac{M \cdot P_R}{N \cdot P_S} = \frac{100K}{40K} = 2.5 \frac{\text{res}}{\text{saibn}}$$

Scan S (N)

∀ s probe hash idx (1.2)

find matching tuples 2.5

$$N = N \cdot P_S (1.2 + 2.5) = 500 + 500 \cdot 80 \cdot (3.7) = \boxed{148,500} \rightarrow \boxed{5 \text{ min}}$$

Block Nested Loop Joins

→ 1 page for streaming the inner S

1 page for output

k pages for holding blocks (of k) of outer R

∀ block of k pages of R

∀ page bs in S

∀ tuple r in k pages of R

∀ tuple s in bs

if $r_i = s_j$ add $\langle r, s \rangle$ to the result

COST

Scan outer R: M I/Os

Scan inner for each blk of R

$$M + \frac{M}{k} \cdot N \rightarrow 1000 + \frac{500 \cdot 1000}{k} \quad k = 100 \text{ pages}$$

$$\rightarrow \boxed{6000 \text{ I/Os}} \quad \boxed{12 \text{ sec}}$$

$$N + \frac{N}{k} \cdot M \rightarrow 500 + \frac{500 \cdot 1000}{k}$$

$$\rightarrow \boxed{5500} \rightarrow \boxed{11 \text{ sec}}$$

• Sort - Merge Join

→ both sorted on the join attribute

useful: ① both or one relations sorted on join attr.

② output should be sorted on join attr.

→ many duplicates may lead to backtracking

$$\underline{\text{Cost}} \quad \text{Sort } R + \text{Sort } S + M + N$$

worst case? $\underline{M \cdot N}$ if all is equal

$$\text{Cost} \quad (M+N) \cdot 2 \cdot \# \text{ passes} + M + N$$

2 passes?

$$\left\lceil \frac{N}{B} \right\rceil = B-1 \approx \frac{N}{B} = B-1 \Rightarrow B^2 - B - N = 0$$

$$B \approx \sqrt{N} + 1 = 33$$

$$\text{Cost} = (M+N) \cdot S = 1500 \cdot S = \boxed{7500} \text{ I/Os} \rightarrow \boxed{15 \text{ sec}}$$

$$\text{BNLJ w/ 33 buffers} \quad M + \frac{M \cdot N}{k} = 1000 + \frac{500 \cdot 1000}{33} \approx \boxed{1000 + 15151}$$

$$N + \frac{M \cdot N}{k} = 500 + \frac{500 \cdot 1000}{33} \approx \boxed{500 + 15151}$$

if $k=100$ SMJ cannot do better than $\boxed{7500}$

BNLJ will do as low as $\boxed{5500}$

Refined Sort-Merge Join

assume $B > \sqrt{M}$ and $B > \sqrt{N}$

after pass 0

$$R \rightarrow \frac{M}{B} \text{ runs} \quad B > \sqrt{M} \Rightarrow \frac{1}{B} < \frac{1}{\sqrt{M}} \Rightarrow \frac{M}{B} < \sqrt{M} < B$$

$$S \rightarrow \frac{N}{B} \text{ runs} \quad B > \sqrt{N} \Rightarrow \frac{N}{B} < \sqrt{N} < B$$

after pass 0 either R, S #runs $< B$


consider using replacement sort

it results to runs with size $\approx 2B$

sorted runs after pass 0 using replacement sort

$$R \rightarrow \frac{M}{2B} < \frac{B}{2} \quad S \rightarrow \frac{N}{2B} < \frac{B}{2}$$

we allocate a buffer per sorted run per file



$$\text{Cost} = (M+N) \cdot 3$$

Read R \rightarrow writing $< B/2$ # runs of R $2 \cdot M$

Read S \rightarrow writing $< B/2$ # runs of S $2 \cdot N$

Read R and S and merge on the fly : $M+N$

$$(M+N) \cdot 3 = \boxed{4500} \text{ I/Os} \rightarrow \boxed{9s}$$